



Exhibit B



5 SECOND FLOOR DEMOLITION PLAN

D2.1 : D2.1 1/2" = 1' - 0"

#	DEMOLITION KEYNOTES
①	DEMO ROOM SIDE WALL FINISH AS REQ. FOR (N) CARD READER AND HARDWARE.
②	REMOVE AND SALVAGE (E) CARD READER AND ACCESS PANEL TO OWNER.
③	REMOVE AND SALVAGE (E) DOOR STOPS TO DOOR 208.1 ON SIDES AND TOP OF DOOR FRAME FOR RE-LOCATION.
④	REMOVE ONE SECTION (FOUR STACKS) OF LOCKERS INCLUDING BASE, SLOPED HOOD, END PANEL AND WALL ANCHORS. SALVAGE END PANEL FOR RE-USE IN (N) WORK. SALVAGE LOCKERS, BASE, SLOPED HOOD, AND WALL ANCHORS TO OWNER.
⑤	REMOVE AND SALVAGE (E) DOOR AND DOOR HARDWARE TO BE RE-LOCATED. TRANSOM AND DOOR FRAME TO REMAIN.
⑥	REMOVE (E) CORNER GUARD IN PREPARATION FOR (N) WALL.
⑦	CUT AND REMOVE CARPET IN COORDINATION WITH (N) WALL CONSTRUCTION. MAINTAIN CARPET AT (N) DOOR LOCATION.
⑧	CUT AND REMOVE (E) CEILING TILE AND METAL GRID AS REQUIRED FOR NEW WALL CONSTRUCTION.
⑨	CUT, REMOVE, AND SALVAGE PORTION OF (E) PICTURE RAIL TO ACCOMMODATE (N) WORK.
⑩	(E) LIGHT. REFERENCE ELECTRICAL DRAWINGS.
⑪	(E) SMOKE ALARM, SPRINKLER, AND MECHANICAL DIFFUSER. REFERENCE MECHANICAL AND ELECTRICAL DRAWINGS.
⑫	REMOVE (E) SIGN, SALVAGE TO OWNER.
⑬	REMOVE AND SALVAGE (E) FLOOR-MOUNTED DOOR STOP TO BE RE-LOCATED.
⑭	REMOVE AND SALVAGE SECTION OF (E) WOOD BASEBOARD TO BE RE-INSTALLED IN (N) WORK.
⑮	(E) FIRE EXTINGUISHER CABINET TO REMAIN.
⑯	(E) PICTURE RAIL TO REMAIN.
⑰	(E) SIGN TO REMAIN, NO WORK.



7 SECOND FLOOR DEMOLITION REFLECTED CEILING PLAN


D2.1 : D2.1 1/2" = 1' - 0"

- DEMOLITION GENERAL NOTES**
- FIELD VERIFY ALL DIMENSIONS. DO NOT SCALE DRAWINGS. VERIFY EXISTING CONDITIONS AND NOTIFY THE ARCHITECT OF ANY DISCREPANCIES PRIOR TO COMMENCING WORK.
 - COORDINATE ALL DEMOLITION WORK WITH EXISTING CONDITIONS AND NEW WORK INDICATED.
 - REFER TO MECHANICAL AND ELECTRICAL DRAWINGS FOR ADDITIONAL DEMOLITION WORK, TYP.
 - ANY ITEM SHOWN OR REFERENCED IN ONE INSTANCE SHALL BE AS IF SHOWN IN ALL INSTANCES.
 - REFERENCE TO DEMOLITION PHOTOGRAPH.
 - SALVAGE ALL EXISTING SIGNAGE TO OWNER WITHIN AREAS OF WORK, TYP. CLEAN SURFACE AT ALL FORMER SIGNAGE LOCATIONS TO REMOVE ADHESIVE AND/OR TAPE(S) IN ENTIRETY.
 - PROTECT ALL EXISTING SURFACES AND FINISHES TO REMAIN, TYP.
 - SALVAGE ALL EXISTING OAK STANDING AND RUNNING WOOD TRIM, INCLUDING, BUT NOT LIMITED TO DOOR STOPS, PICTURE RAILS, AND WALL BASE, WITHIN AREA OF WORK, U.N.O. PREP FOR RE-INSTALLATION. SALVAGE ALL UNUSED OAK STANDING AND RUNNING TRIM TO OWNER, TYP.
 - PROTECT EXISTING MARBLE WAINSCOTING IN ROTUNDA SPACES.
 - PROTECT ALL COURTHOUSE HISTORIC MOSAIC FLOOR TILE DURING WORK, TYP.
 - SALVAGE EXISTING PANELED OAK DOOR, (E) FRAMES, TRANSOMS, GLAZING, TRIM, DOOR AND TRANSOM HARDWARE TO REMAIN. REPAIR AS INDICATED, FOR RE-USE AT NEW LOCATION.

LEGEND

HATCH INDICATES APPROXIMATE AREA TO CUT CARPET IN COORDINATION WITH (N) WALL CONSTRUCTION.

2 0 2 4
SCALE OF FEET 1/2" = 1'-0"



SECOND FLOOR DEMOLITION PLAN & REFLECTED CEILING PLAN
MISSOULA COUNTY COURTHOUSE SELF HELP MOVE
200 WEST BROADWAY, 2ND FLOOR

sheet project owner

project #

revision

date

phase

CONSTRUCTION DOCUMENTS



Page 2/10

issue date
04.24.2025


D2.1

Exhibit B



5 DEMOLITION - PHOTOGRAPH

D2.1 : D2.1 NTS




6 DEMOLITION - PHOTOGRAPH

D2.1 : D2.1 NTS




7 DEMOLITION - PHOTOGRAPH

D2.1 : D2.1 NTS



8 DEMOLITION - PHOTOGRAPH

D2.1 : D2.1 NTS




13 DEMOLITION - PHOTOGRAPH

D2.1 : D2.1 NTS

DEMOLITION GENERAL NOTES

- FIELD VERIFY ALL DIMENSIONS. DO NOT SCALE DRAWINGS. VERIFY EXISTING CONDITIONS AND NOTIFY THE ARCHITECT OF ANY DISCREPANCIES PRIOR TO COMMENCING WORK.
- COORDINATE ALL DEMOLITION WORK WITH EXISTING CONDITIONS AND NEW WORK INDICATED.
- REFER TO MECHANICAL AND ELECTRICAL DRAWINGS FOR ADDITIONAL DEMOLITION WORK TYP.
- ANY ITEM SHOWN OR REFERENCED IN ONE INSTANCE SHALL BE AS IF SHOWN IN ALL INSTANCES.
- REFERENCE TO DEMOLITION PHOTOGRAPH.
- SALVAGE ALL EXISTING SIGNAGE TO OWNER WITHIN AREAS OF WORK, TYP. CLEAN SURFACE AT ALL FORMER SIGNAGE LOCATIONS TO REMOVE ADHESIVE AND/OR TAPE(S) IN ENTIRETY.
- PROTECT ALL EXISTING SURFACES AND FINISHES TO REMAIN, TYP.
- SALVAGE ALL EXISTING OAK STANDING AND RUNNING WOOD TRIM, INCLUDING, BUT NOT LIMITED TO, DOOR STOPS, PICTURE RAILS, AND WALL BASE, WITHIN AREA OF WORK, U.N.O. PREP FOR RE-INSTALLATION. SALVAGE ALL UNUSED OAK STANDING AND RUNNING TRIM TO OWNER.
- PROTECT EXISTING MARBLE WAINSCOTING IN ROTUNDA SPACES.
- PROTECT ALL COURTHOUSE HISTORIC MOSAIC FLOOR TILE DURING WORK, TYP.
- SALVAGE EXISTING PANELED OAK DOOR, (E) FRAMES, TRANSOMS, GLAZING, TRIM, DOOR AND TRANSOM HARDWARE TO REMAIN. REPAIR AS INDICATED, FOR RE-USE AT NEW LOCATION.

LEGEND

 HATCH INDICATES APPROXIMATE AREA TO PREPARE FOR (N) WALL AND DOOR CONSTRUCTION.

MISSOULA COUNTY COURTHOUSE SELF HELP MOVE 200 WEST BROADWAY, 2ND FLOOR

sheet

project

owner

project #

25004.0

revision


date

phase

CONSTRUCTION DOCUMENTS



Exhibit B




9 SECOND FLOOR CONSTRUCTION PLAN

A2.1 : A2.1 1/2" = 1'-0"

NEW WORK KEYNOTES

- ① (E) CARPET UNDERNEATH LOCKERS.
- ② DUTCHMAN REPAIR (E) DOOR FRAME DUE TO REMOVAL OF HARDWARE AND WOOD STOPS. SAND, PREP, AND REFINISH ENTIRE CASED OPENING FRAME. COLOR TOUCH UP 'AGED OAK' AS REQ.
- ③ RE-INSTALL (E) SALVAGED DOOR AND HARDWARE TO (N) LOCATION.
- ④ (N) CARD READER LOCATION.
- ⑤ NOT USED.
- ⑥ (N) WALL SEE A9.1 FOR WALL TYPE.
- ⑦ (N) WOOD DOOR JAMB & FRAME TO MATCH IN-KIND TO (E) DOOR JAMB AND FRAME CONDITIONS AT RE-LOCATED DOOR.
- ⑧ RE-LOCATE (E) DOOR STOPS TO (N) 208A.1 DOOR LOCATION.
- ⑨ (E) FIRE EXTINGUISHER TO REMAIN.
- ⑩ RELOCATED (E) LIGHT IN ACT CEILING. COORDINATE WITH ELECTRICAL DRAWINGS.
- ⑪ (N) PICTURE RAIL FOR (N) WALL MATCH IN-KIND TO (E). REUSE SALVAGED PICTURE RAIL WHERE APPLICABLE, MITER 45 DEGREES AT CORNERS, FINISH (N) AND (E) TO MATCH IN-KIND TO (E).
- ⑫ PATCH AND REPAIR WALL FINISHES DUE TO INSTALLATION OF (N) CARD READER AND DOOR HARDWARE.
- ⑬ RE-INSTALL (E) SALVAGED ACT TILE AND DETAIL GRID CEILING TO COORDINATE WITH (N) WALL CONSTRUCTION.
- ⑭ (E) MECHANICAL DIFFUSER, SMOKE ALARM, AND SPRINKLER. REFERENCE MECHANICAL AND ELECTRICAL DRAWINGS FOR ADDITIONAL WORK.
- ⑮ RE-INSTALL SALVAGED FLOOR-MOUNTED DOOR STOP IN (N) LOCATION.



11 SECOND FLOOR REFLECTED CEILING PLAN

A2.1 : A2.1 1/2" = 1'-0"

GENERAL NOTES


- 1. REFERENCE SHEET A9.1 FOR WALL TYPES, DOOR AND DOOR FRAME TYPES.
- 2. REFERENCE SHEET A9.1 FOR STANDING AND RUNNING TRIM PROFILES.
- 3. REFERENCE MECHANICAL AND ELECTRICAL DRAWINGS FOR ADDITIONAL WORK.

2 0 2 4
SCALE OF FEET
1/2" = 1'-0"

Page 4/10

issue date
04.24.2025

A2.1




SECOND FLOOR CONSTRUCTION PLAN & REFLECTED CEILING
PLAN
MISSOULA COUNTY COURTHOUSE SELF HELP MOVE
200 WEST BROADWAY, 2ND FLOOR


sheet project owner
project # 25004.0 date
revision
phase CONSTRUCTION DOCUMENTS




Exhibit B




1 HALL 208 - DEMOLITION NORTH ELEVATION





6 HALL 208 / 208A NORTH ELEVATION




2 HALL 208 - DEMOLITION EAST ELEVATION



3 HALL 208 - DEMOLITION SOUTH ELEVATION




4 HALL 208 - DEMOLITION WEST ELEVATION




5 NORTH HALL 205 - DEMOLITION WEST ELEVATION


7 HALL 208A EAST ELEVATION



8 HALL 208 / 208A SOUTH ELEVATION



9 HALL 208A WEST ELEVATION



10 NORTH HALL 205 WEST ELEVATION

DEMOLITION KEYNOTES

- ① DEMO ROOM SIDE WALL FINISH AS REQ. FOR (N) CARD READER AND HARDWARE.
- ② REMOVE AND SALVAGE (E) CARD READER AND ACCESS PANEL TO OWNER.
- ③ REMOVE AND SALVAGE (E) DOOR STOPS TO DOOR 208.1 ON SIDES AND TOP OF DOOR FRAME FOR RE-LOCATION.
- ④ REMOVE ONE SECTION (FOUR STACKS) OF LOCKERS INCLUDING BASE, SLOPED HOOD, END PANEL, AND WALL ANCHORS. SALVAGE END PANEL FOR RE-USE IN (N) WORK. SALVAGE LOCKERS, BASE, SLOPED HOOD, AND WALL ANCHORS TO OWNER.
- ⑤ REMOVE AND SALVAGE (E) DOOR AND DOOR HARDWARE TO BE RE-LOCATED. TRANSOM AND DOOR FRAME TO REMAIN.
- ⑥ REMOVE (E) CORNER GUARD IN PREPARATION FOR (N) WALL.
- ⑦ NOT USED.
- ⑧ NOT USED.
- ⑨ CUT, REMOVE, AND SALVAGE PORTION OF (E) PICTURE RAIL TO ACCOMMODATE (N) WORK.
- ⑩ REMOVE AND SALVAGE SECTION OF (E) WOOD BASEBOARD TO BE RE-INSTALLED IN (N) WORK.
- ⑪ REMOVE AND SALVAGE (E) FLOOR-MOUNTED DOOR STOP TO BE RE-LOCATED.
- ⑫ (E) FIRE EXTINGUISHER CABINET TO REMAIN.
- ⑬ (E) PICTURE RAIL TO REMAIN.
- ⑭ (E) SIGN TO REMAIN, NO WORK.
- ⑮ REMOVE (E) SIGN, SALVAGE TO OWNER.
- ⑯ DEMO (E) WALL FINISHES TO COORDINATE WITH (N) CONSTRUCTION.
- ⑰ (E) LOCKERS, PROTECT IN PLACE.
- ⑱ (E) MARBLE WALL BASE TO REMAIN.

NEW WORK KEYNOTES

- ① (N) CARD READER LOCATION.
- ② DUTCHMAN REPAIR (E) DOOR FRAME DUE TO REMOVAL OR HARDWARE, SAND, PREP, AND REFINISH ENTIRE CASED OPENING FRAME. COLOR TOUCH UP AGED OAK AS REQ.
- ③ RE-INSTALL (E) SALVAGED DOOR AND HARDWARE TO (N) LOCATION.
- ④ NOT USED.
- ⑤ NOT USED.
- ⑥ (N) WALL, SEE A3.1 FOR WALL TYPE.
- ⑦ (N) WOOD DOOR JAMB & FRAME TO MATCH IN-KIND TO (E) DOOR JAMB AND FRAME CONDITIONS AT RELOCATED DOOR.
- ⑧ RE-LOCATE (E) DOOR STOPS TO (N) 208A.1 DOOR LOCATION.
- ⑨ (N) PICTURE RAIL FOR (N) WALL MATCH IN-KIND TO (E). REUSE SALVAGED PICTURE RAIL WHERE APPLICABLE, MITER 45 DEGREES AT CORNERS.
- ⑩ (N) WOOD BASEBOARD TO ACCOMMODATE (N) WALL. MATCH IN-KIND TO (E). USE SALVAGED BASEBOARD WHERE APPLICABLE.
- ⑪ RE-INSTALL SALVAGED FLOOR-MOUNTED DOOR STOP IN (N) LOCATION.
- ⑫ (E) FIRE EXTINGUISHER CABINET TO REMAIN.
- ⑬ (E) PICTURE RAIL TO REMAIN.
- ⑭ (E) DOOR AND FRAME, COORDINATE WITH (N) CARD READER.
- ⑮ (E) LOCKERS, PROTECT IN PLACE.
- ⑯ PRIME AND PAINT (E) AND (N) WALL EDGE TO EDGE, TOP TO BOTTOM, COLOR TO MATCH (E).
- ⑰ (E) MARBLE WALL BASE TO REMAIN.
- ⑱ (E) TRANSOM AND FRAME TO REMAIN.
- ⑲ INFILL AND FINISH WALL TO MATCH (E) ADJACENT CONDITIONS, PRIME AND PAINT WALL EDGE TO EDGE, TOP TO BOTTOM.

LEGEND

HATCH INDICATES AREA OF MARBLE BASEBOARD.

HATCH INDICATES AREA OF WOOD BASEBOARD.

4 0 4 8
SCALE OF FEET
1/4" = 1'-0"

2 0 2 4
SCALE OF FEET
1/2" = 1'-0"

Page 5/10

issue date
04.24.2025

A6.1




sheet DEMO & NEW CONSTRUCTION INTERIOR ELEVATIONS
project MISSOULA COUNTY COURTHOUSE SELF HELP MOVE
owner MISSOULA COUNTY, 200 WEST BROADWAY, 2ND FLOOR
dimensions 59802

project # 25004.0
revision date


phase CONSTRUCTION DOCUMENTS




Exhibit B




1 DOOR FRAME - (E) FIXED TRANSOM, MARBLE WAINSCOT
A9.1 : A9.1 1/2" = 1' - 0"




2 DOOR FRAME - TYPE A2
A9.1 : A9.1 1/2" = 1' - 0"




3 DOOR FRAME - (E), FIXED TRANSOM, MARBLE BASE
A9.1 : A9.1 1/2" = 1' - 0"




4 RE-LOCATED DOOR
A9.1 : A9.1 1/2" = 1' - 0"




5 TYP. CP-PR
A9.1 : A9.1 3" = 1' - 0"



6 PICTURE RAIL - TYPE CP-PR
A9.1 : A9.1 1' - 0" = 1' - 0"




7 TYP. WOOD BASE PROFILE, CP-WB
A9.1 : A9.1 6" = 1' - 0"




9 TYP. DOOR TRIM, TYPE CP-WT
A9.1 : A9.1 1' - 0" = 1' - 0"

WALL TYPES LEGEND



INTERIOR COURTHOUSE WALL
WALL FINISH, LEVEL 5 TO MATCH (E)
5/8" TYPE X GYP. BOARD
3 1/2" WOOD STUD W/ SOUND BATT INSULATION
5/8" TYPE X GYP. BOARD
WALL FINISH, LEVEL 5 TO MATCH (E)

NOTE: PRIME & PAINT GYP. BOARD, 3 COATS,
COLORS TO MATCH (E).



12 NEW WALL - WOOD BASE
A2.1 : A9.1 3" = 1' - 0"

DOOR SCHEDULE										
DOOR	DESCRIPTION	SIZE (W X L X THICKNESS)			DOOR		FRAME		HARDWARE GROUP	REMARKS
		TYPE	MATERIAL	FINISH	TYPE	MATERIAL	TYPE	MATERIAL		
206.1	SELF HELP DOOR	(E)							C02	(E) TRANSOM IN FRAME
208.1	HALL 208 DOOR FROM NORTH HALL									NO WORK
208A.1	HALL DOOR BETWEEN 208 AND 208A	RELOCATED	(E)	(E)	A2	WOOD	TRANSPARENT	MATCH (E)	C12	(N) RELOCATED DOOR & (N) DOOR FRAME
211.1	JURY RESTROOM DOOR									NO WORK
213.1	BAILIFF DOOR	(E)							C06	(E) DOOR & DOOR FRAME W/ (N) HARDWARE

DOOR HARDWARE SCHEDULE

DOOR 208A.1 HARDWARE GROUP C12

- HINGES: (E) SALVAGE AND REUSE (E)
- LEVER: (E) SALVAGE AND REUSE (E) SCHLAGE ND92PD SPA
- FLOOR DOME STOP: SALVAGE AND REUSE (E)
- ELECTRIC STRIKE: SALVAGE AND REUSE (E) HES 7000-791 LBSM 12VDC
- CARD READER: (N) CARD READER, COORD W OWNER

DOOR 206.1 HARDWARE GROUP C02


- HINGES: (E)
- LEVER: (E) SCHLAGE ND50PD SPA
- FLOOR DOME STOP: (E)
- ELECTRIC STRIKE: HES 7000-791 LBSM 12VDC
- CARD READER: (N) CARD READER, COORDINATE W OWNER

DOOR 213.1 HARDWARE GROUP C06

- HINGES: (E) HISTORIC
- LEVER: (E) HISTORIC KNOB MORTICE LATCH
- DEADBOLT: (E) SCHLAGE B662P
- FLOOR DOME STOP: (E)
- ELECTRIC STRIKE: HES 7000-791 LBSM 12VDC
- CARD READER: (N) CARD READER, COORDINATE W OWNER

KEYNOTES

- | | |
|-----|--|
| (1) | (N) WOOD DOOR JAMB & FRAME TO MATCH IN-KIND TO (E) DOOR JAMB AND FRAME CONDITIONS AT RE-LOCATED DOOR. |
| (2) | REPAIR (E) DOOR JAMB. FILL IN LATCH AND HINGE HOLES. SAND, PREP, RESTORE FRAME FINISHES. COLOR TOUCH UP AGED OAK AS REQ. |



WALL TYPES, FRAME TYPES, DOOR TYPES, MILLWORK PROFILES,
DOOR & HARDWARE SCHEDULES
MISSOULA COUNTY COURTHOUSE SELF HELP MOVE
200 WEST BROADWAY, 2ND FLOOR
MISSOULA COUNTY, 200 WEST BROADWAY STREET, MISSOULA, MT 59802

sheet project owner
project # 25004.0
revision date
phase CONSTRUCTION DOCUMENTS



Page 6/10

issue date
04.24.2025

A9.1

Exhibit B

GENERAL LEGEND			
NOTE: THESE ARE STANDARDIZED SYMBOLS LEGENDS. AS SUCH, ALL SYMBOLS SHOWN MAY NOT APPEAR ON OR WITHIN THIS SET OF CONTRACT DOCUMENTS.			
SYMBOL	NAME	SYMBOL	NAME
(X)	SPECIFIC SHEET NOTE	(X)	SECTION REFERENCE NUMBER
(XX)	PLUMBING FIXTURE IDENTIFICATION	(X)	SECTION REFERENCE SHEET
(X XX)	EQUIPMENT MARK	(X)	ON DEMOLITION PLANS:
XX	"X" INDICATES TYPE	(X)	INDICATES ITEMS TO BE REMOVED
XXX	"XX" INDICATES NUMBER	(X)	POINT OF NEW CONNECTION
	G-R-D IDENTIFICATION		
	CFM AIR FLOW		

MECHANICAL AND PLUMBING LEGEND			
DUCTWORK - DRYSIDE		PIPING / PLUMBING - WETSIDE	
SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
12" x 6"	RECTANGULAR DUCT (VIEW WIDTH x VIEW DEPTH)	HWS	HEATING WATER SUPPLY
12"	ROUND DUCT	HWR	HEATING WATER RETURN
12" x 6"	oval DUCT (VIEW WIDTH x VIEW DEPTH)	CWS	CHILLED WATER SUPPLY
diagonal lines	ACOUSTICALLY LINED DUCT	CWR	CHILLED WATER RETURN
cross-hatch	EXTERIOR INSULATED DUCT	CTWS	COOLING TOWER WATER SUPPLY
cross-hatch	EXTERIOR INSULATED AND ACOUSTICALLY LINED DUCT	CTWR	COOLING TOWER WATER RETURN
vertical lines	FLEXIBLE ROUND DUCT	HPS	HEAT PUMP SOURCE SUPPLY
blue circle with X	VERTICAL SUPPLY AIR OR POSITIVE PRESSURE DUCTS	HPSR	HEAT PUMP SOURCE RETURN
pink circle with X	VERTICAL RETURN AIR OR NEGATIVE PRESSURE DUCTS	HPLS	HEAT PUMP LOAD SUPPLY
green circle with X	VERTICAL EXHAUST AIR DUCTS	HPLR	HEAT PUMP LOAD RETURN
blue square	MANUAL BALANCING / VOLUME DAMPER	HPS	HIGH PRESSURE STEAM
blue square	PARALLEL BLADE DAMPER	HSC	HIGH PRESSURE STEAM CONDENSATE
blue square	OPPOSED BLADE DUCT	MPS	MEDIUM PRESSURE STEAM
blue square	MOTOR ACTUATED DAMPER	MPC	MEDIUM PRESSURE STEAM CONDENSATE
blue square	DUCT MOUNTED VERTICAL FIRE DAMPER	LPS	LOW PRESSURE STEAM
blue square	DUCT MOUNTED VERTICAL FIRE / SMOKE DAMPER	LPC	LOW PRESSURE STEAM CONDENSATE
blue square	DUCT MOUNTED HORIZONTAL FIRE OR FIRE / SMOKE DAMPER	RS	REFRIGERANT SUCTION
blue square	STRAIGHT TAKE-OFF	RL	REFRIGERANT LIQUID
blue square	CONICAL TAKE-OFF	COND	CONDENSATE
blue square	HIGH EFFICIENCY TAKE-OFF (HETO)	NG	NATURAL GAS
blue square	MITERED RECTANGULAR DUCT ELBOW WITH TURNING VANES	LPG	LIQUEFIED PETROLEUM GAS (PROPANE)
blue square	SHARP-THROAT RADIUS-HEEL RECTANGULAR DUCT ELBOW	DCW	DOMESTIC COLD WATER (DCW)
blue square	1.0 RADIUS AND 1.5 RADIUS SMOOTH ROUND OR OVAL ELBOW	DHW	DOMESTIC HOT WATER (DHW)
blue square	1.0 RADIUS AND 1.5 RADIUS 3-GORE ROUND OR OVAL ELBOW	DHC	DOMESTIC HOT CIRCULATION (DHC)
blue square	1.0 RADIUS AND 1.5 RADIUS 5-GORE ROUND OR OVAL ELBOW	V	VENT - SANITARY
TEMPERATURE CONTROLS			
SYMBOL	DESCRIPTION		
RTU-1	THERMOSTAT - LABEL INDICATES ASSOCIATED SYSTEM		
RZ-1	SENSOR - LABEL INDICATES ASSOCIATED SYSTEM		
FC-1	HUMIDISTAT - LABEL INDICATES ASSOCIATED SYSTEM		
AHU-1	CARBON DIOXIDE SENSOR - LABEL INDICATES ASSOCIATED SYSTEM		
P	PRESSURE SENSOR		
DP	DIFFERENTIAL PRESSURE SENSOR		
FS	FLOW SWITCH		
CS	CURRENT SENSOR		

NOTE: THESE ARE STANDARDIZED SYMBOLS LEGENDS. AS SUCH, ALL SYMBOLS SHOWN MAY NOT APPEAR ON OR WITHIN THIS SET OF CONTRACT DOCUMENTS.

PROVIDE SUBMITTALS FOR ALL COMPONENTS OF THE MECHANICAL AND PLUMBING SYSTEMS AS NOTED BELOW. ANY MATERIALS NOT SUBMITTED ON MAY BE REJECTED IN THE FIELD AND REQUIRE THE INSTALLER TO REMOVE AND REPLACE, AT THEIR COST, AS DEEMED NECESSARY BY THE ENGINEER. FOR RESIDENTIAL PROJECTS: NO EQUIPMENT SHALL BE 3-PHASE.

REFER TO SPECIFICATIONS FOR ALL MECHANICAL AND PLUMBING RELATED WORK. ALL WORK SHALL BE IN STRICT ACCORDANCE WITH THE PLANS, SPECIFICATIONS, AND MANUFACTURER'S WRITTEN INSTRUCTIONS. ALL DEVIATIONS FROM THE PLANS AND/OR SPECIFICATIONS SHALL REQUIRE WRITTEN PRIOR APPROVAL FROM THE ENGINEER.

SUBMITTALS SHALL BE IN PDF FORMAT ONLY. PARTIAL OR INCOMPLETE SUBMITTALS AND PAPER COPIES WILL NOT BE REVIEWED. SUBMITTALS SHALL BE COMBINED INTO ONE FILE, WITH EACH SECTION LABELED ACCORDING TO IT'S RESPECTIVE SPECIFICATION SECTION.

ABBREVIATIONS


(E)	EXISTING (U.S. or I.J.S.) IN-EXIST SPACE	HHW	HEATING HOT WATER
(N)	NEW	HWR	HEATING WATER RETURN
(NL)	NEW LOCATION	HWS	HEATING WATER SUPPLY
(RE)	RELOCATE or RELOCATED	LAV	LAVATORY
A.D.	ACCESS DOOR	LCUV	LARGE CAPACITY UNIT VENTILATOR
A.F.F.	ABOVE FINISH FLOOR	MA	MIXED AIR
A.F.G.	ABOVE FINISH GRADE	MAX.	MAXIMUM
AHU	AIR HANDLING UNIT	MC	MECHANICAL CONTRACTOR
ARCH	ARCHITECT or ARCHITECTURAL	MECH.	MECHANICAL
CA	COMPRESSED AIR	MFR.	MANUFACTURER
CC	COOLING COIL	MIN.	MINIMUM
CFM	CUBIC FEET PER MINUTE	N.C.	NORMALLY CLOSED
CH	CABINET HEATER	N.O.	NORMALLY OPEN
CHWR / CWS	CHILLED WATER RETURN	O.C.	ON CENTER
CHWS / CWS	CHILLED WATER SUPPLY	OA	OUTSIDE AIR
CO or C.O.	CLOSED	PG	PROPYLENE GLYCOL
CONT.	CONTINUATION	PICV	PRESSURE INDEPENDENT CONTROL VALVE
COTG	CLEANOUT TO GRADE	RA	REACH
CUH	CABINET UNIT HEATER	RDL	ROOF DRAIN LEADER
DOW	DOMESTIC COLD WATER	RDO	ROOF DRAIN OVERFLOW
DHW	DOMESTIC HOT WATER	REQ'D	REQUIRED
DHC	DOMESTIC HOT WATER RECIRCULATION	RHC	REHEAT COIL
DF	DRINKING FOUNTAIN	S.M.	SHEET METAL
EA	EXHAUST AIR	S.S.	STAINLESS STEEL
EC	ELECTRICAL CONTRACTOR	SA	SUPPLY AIR
EF	EXHAUST FAN	SIM.	SIMILAR
FA	FRESH AIR	SPEC.	SPECIFICATION or SPECIFIED
FC	FAN COIL	TA	TRANSFER AIR
FD	FLOOR DRAIN	TYP.	TYPICAL
FE	FIRE EXTINGUISHER	U.N.O.	UNLESS NOTED OTHERWISE
FEC	FIRE EXTINGUISHER CABINET	UH	UNIT HEATER
FF / FINFLR	FLOOR FF	UR	URINAL
FS	FIRE SPRINKLER	UV	UNIT VENTILATOR
FT	FIRE TUBE	VFD	VARIABLE FREQUENCY DRIVE
G.C.	GENERAL CONTRACTOR	V	VENT
HB	HOSE BIBB	VTR	VENT THROUGH ROOF
HC	HEATING COIL	WC	WATER CLOSET
		WS / WF	WASH SINK/FOUNTAIN (LAVATORY)

DRAWING INDEX

MISSOULA COUNTY COURTHOUSE SELF HELP MOVE

200 WEST BROADWAY
MISSOULA, MT 59802

Axiom Engineering Group #: 24045
Project Manager Ormond Allred



NOTE:
HYDRONIC SYSTEM AS WELL AS AIR BALANCE OF SYSTEMS IS REQUIRED. DELIVER TESTING AND BALANCE REPORTS TO ENGINEER FOR REVIEW PRIOR TO PROJECT COMPLETION.

THIS PROJECT WILL REQUIRE COMMISSIONING TO ENSURE THE DESIGNED SYSTEMS ARE OPERATING THE WAY THE ENGINEERS, DESIGNERS AND OWNER INTEND.



MISSOULA COUNTY COURTHOUSE SELF HELP MOVE
200 WEST BROADWAY, 2ND FLOOR
owner MISSOULA COUNTY, 200 WEST BROADWAY STREET, MISSOULA, MT 59802

sheet project
project # 25004.0
AEG # 24045
revision date

phase
CONSTRUCTION DOCUMENTS



Page 7/10

issue date
04.24.2025

M0.1

Exhibit B

MECHANICAL SPECIFICATIONS

PART 1 - GENERAL

1.1 GENERAL INTENT

- A. THE INTENTION OF THE CONTRACT DOCUMENTS IS TO INCLUDE ALL LABOR AND MATERIALS, AND EQUIPMENT, NECESSARY, OR REASONABLY INFERABLE AS BEING NECESSARY, FOR FURNISHING, INSTALLATION AND TESTING, COMPLETE AND READY FOR SAFE OPERATION OF THE SYSTEMS DESCRIBED HEREIN.
- B. SUBMISSION OF A PROPOSAL SHALL BE CONSTRUED AS EVIDENCE THAT THE CONTRACTOR HAS MADE A THOROUGH EXAMINATION OF THE SITE, AND ALL EXISTING CONDITIONS AND LIMITATIONS WHICH AFFECT THIS WORK. LATER CLAIMS SHALL NOT BE MADE FOR LABOR, EQUIPMENT OR MATERIALS REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED, WHICH COULD HAVE BEEN FORESEEN DURING SUCH AN EXAMINATION.
- C. THE DRAWINGS INDICATE DIAGRAMMATICALLY THE EXTENT, GENERAL CHARACTER, AND LOCATION OF THE WORK TO BE PERFORMED, WHERE MINOR ADJUSTMENTS OF THE WORK ARE NECESSARY FOR PURPOSES OF FABRICATION OR INSTALLATION OF ITEMS, THE CONTRACTOR SHALL MAKE SUCH ADJUSTMENTS WITH NO ADDED COMPENSATION, WHERE SUCH ADJUSTMENTS AFFECT FUNCTIONAL OR AESTHETIC DESIGN OF THE WORK, THEY SHALL FIRST BE SUBMITTED TO THE ARCHITECT FOR REVIEW AND APPROVAL.
- D. SITE UTILITIES: THE MECHANICAL DOCUMENTS INDICATE CONNECTION LOCATION OF VARIOUS BUILDING SERVICES. COORDINATE WORK WITH THE SITE UTILITIES CONTRACTOR TO ENSURE PROPER ELEVATION, PIPE SLOPE GRADIENT, PIPE SIZE AND SEPARATION WITHIN TRENCH WORK. NOTIFY ARCHITECT OR ENGINEER OF ANY DISCREPANCY BETWEEN DRAWINGS AND FIELD CONDITIONS.
- E. COMPLY WITH ALL LOCAL AND STATE CODES REGARDING SEISMIC SUPPORT AND ISOLATION. NOT ALL SEISMIC REQUIREMENTS ARE SHOWN ON THESE DRAWINGS. CONTRACTOR SHALL MEET THE REQUIREMENTS OF THE AUTHORITY HAVING JURISDICTION FOR SEISMIC SUPPORT/ISOLATION OF HIS WORK.

1.2 GENERAL COORDINATION

- A. THE CONTRACTOR IS RESPONSIBLE FOR INSTALLATION OF A SATISFACTORY, COMPLETE, AND FULLY OPERATIONAL PIECE OF WORK IN ACCORDANCE WITH TRUE INTENT OF THE DRAWINGS AND SPECIFICATIONS.
- B. CONTRACTOR SHALL CONSULT ALL DRAWINGS FOR THE PROJECT TO DETERMINE THAT THE WORK AND EQUIPMENT WILL FIT AS PLANNED.
- C. THE LOCATION OF PIPING, DUCTS, EQUIPMENT, ETC., SHALL BE CHECKED TO ENSURE CLEARANCE FROM OPENINGS, STRUCTURAL MEMBERS, CABINETS, LIGHTS, OUTLETS AND EQUIPMENT HAVING FIXED LOCATIONS. THIS SHALL BE ACCOMPLISHED PRIOR TO FABRICATION OF PIPE OR DUCTS.
- D. IF, AT ANY TIME, AND IN ANY CASE, CHANGES IN LOCATION OF PIPING, DUCTS, EQUIPMENT, ETC., BECOMES NECESSARY DUE TO EXISTING OBSTACLES OR INSTALLATION OF OTHER TRADES SHOWN ON ANY OF THE PROJECT DRAWINGS AND SUCH CONFLICT COULD HAVE BEEN AVOIDED BY PROPER COORDINATION BETWEEN TRADES OR PROPER PRE-PLANNING OF WORK, SUCH REQUIRED CHANGES SHALL BE MADE BY THE CONTRACTOR AT NO EXTRA COST. THESE CHANGES ARE TO BE RECORDED ON THE RECORD DRAWINGS.
- E. THIS CONTRACTOR IS RESPONSIBLE FOR COORDINATE ALL INCIDENTAL ELECTRICAL INTERCONNECTIONS, CONTROL WIRING, ETC., WHICH ARE NECESSARY FOR SYSTEM OPERATION AND WHICH ARE NOT SPECIFICALLY SHOWN OR OTHERWISE INDICATED ON THE ELECTRICAL DRAWINGS OR SPECIFIED IN DIVISION 26.
- F. ALL ELECTRICAL WORK INCIDENTAL TO OR ACCOMPLISHED UNDER THIS DIVISION SHALL COMPLY WITH ALL REQUIREMENTS OF DIVISION 26.
- G. PLANS ARE DIAGRAMMATIC IN NATURE. CONTRACTOR IS RESPONSIBLE FOR REFERRING TO THE DESIGN DOCUMENTS FOR ALL OTHER DISCIPLINES FOR PROJECT CONSTRUCTION AND OTHER DETAILS WHICH AFFECT THE MECHANICAL INSTALLATION. CONTRACTOR SHALL CONFER WITH ALL OTHER TRADES FOR FINISH ADJACENT TO ITS WORK AND ARRANGE TO HAVE VISIBLE PORTIONS OF THIS WORK (SUCH AS ACCESS DOORS, VALVES, SPRINKLER HEADS, ESCUTCHEONS, ETC.) MERGE WITH THE FINISH IN A MANNER SATISFACTORY TO THE ARCHITECT.
- H. CONTRACTOR SHALL IDENTIFY ALL SERVICEABLE ITEMS (VALVES, DAMPERS, COLS, ETC.) SO THAT THE CEILING SUBCONTRACTOR MAY KNOW WHERE TO INSTALL ACCESS-TYPE PANELS SHOULD NOT BE INSTALLED. THIS CONTRACTOR SHALL PROVIDE ACCESS PANELS FOR HIS WORK UNLESS SPECIFICALLY NOTED ON THE DRAWINGS. ARCHITECT SHALL APPROVE LOCATIONS OF ACCESS PANELS PRIOR TO INSTALLATION.
- I. CEILING HEIGHTS: ARCHITECTURAL DRAWINGS SHALL BE CHECKED FOR CEILING HEIGHTS, WALLS, AND CABINETS THAT ARE INTENDED TO CONCEAL WORK OF THIS SECTION. WHERE CONFLICTS OCCUR, THE ARCHITECT SHALL BE NOTIFIED PRIOR TO INSTALLATION OF THE WORK. LOCATION OF EXPOSED WORK SUCH AS LIGHTS, DIFFUSERS, SPEAKERS, SPRINKLER HEADS TAKE PRIORITY OVER CONCEALED WORK.
- J. CONTRACTOR SHALL EXERCISE CARE TO MINIMIZE ANY DISTURBANCE TO ADJACENT AREAS OF THE BUILDING WHICH ARE TO REMAIN IN OPERATION. ISOLATE WORK AREAS BY TEMPORARY PARTITIONS, TARP, ETC. TO KEEP DUST AND DIRT IN THE CONSTRUCTION AREA.
- K. PROVIDE ALL NECESSARY FLASHING, SEALING, ETC. TO MAINTAIN THE WATERPROOF INTEGRITY OF THE BUILDING AS REQUIRED BY THE INSTALLATION OR REMOVAL OF ITEMS AS REQUIRED BY THIS SCOPE OF WORK.
- L. INSTALL ALL WORK OF THIS SCOPE TO BE READILY ACCESSIBLE FOR OPERATION, MAINTENANCE, AND REPAIR. MINOR DEVIATIONS FROM THE DRAWINGS MAY BE MADE TO ACCOMPLISH THIS, BUT CHANGES INVOLVING OTHER TRADES MAY NOT BE MADE WITHOUT PRIOR APPROVAL.
- M. ALL PENETRATIONS MADE THROUGH RATED ASSEMBLIES TO ACCOMMODATE WORK OF THIS SECTION, MUST BE SEALED TO MAINTAIN THE RATING OF SUCH ASSEMBLY BY A U.L. RECOGNIZED SEALING METHOD.
- N. PROVIDE ALL CUTTING AND PATCHING REQUIRED FOR INSTALLATION OF THIS WORK. COORDINATE ALL BLOCKING, SUPPORT, ETC., NECESSARY FOR THE INSTALLATION OF THIS WORK WITH THE GENERAL CONTRACTOR.

1.3 CODES, STANDARDS, PERMITS, AND FEES

- A. ALL PERTINENT CODES AND REGULATIONS GOVERNING OR RELATING TO ANY PORTION OF THIS WORK ARE HEREBY INCORPORATED INTO AND MADE A PART OF THESE SPECIFICATIONS. THEIR PROVISIONS SHALL BE CARRIED OUT BY THE CONTRACTOR, WHO SHALL INFORM THE ARCHITECT IN WRITING PRIOR TO SUBMITTING A BID, OF ANY WORK OR MATERIALS WHICH VIOLATE ANY OF THE ENFORCED LAWS, CODES, OR REGULATIONS. IF THE CONTRACTOR PERFORMS ANY WORK CONTRARY TO SUCH LAWS, ORDINANCES, RULES AND REGULATIONS, HE SHALL ASSUME FULL RESPONSIBILITY, AND SHALL BEAR ALL COSTS ASSOCIATED WITH BRINGING WORK INTO COMPLIANCE.
- B. WHERE DRAWINGS OR SPECIFICATIONS CALL FOR MATERIAL OR CONSTRUCTION OF A BETTER QUALITY OR HIGHER CAPACITY THAN REQUIRED BY THE ABOVE-MENTIONED CODES AND STANDARDS, THE PROVISIONS OF THE DRAWINGS OR SPECIFICATIONS SHALL TAKE PRECEDENCE OVER THE REQUIREMENTS OF THE CODES AND STANDARDS.
- C. THE RESPECTIVE SUB-CONTRACTOR, AT HIS EXPENSE, SHALL OBTAIN ALL PERMITS AND FEES REQUIRED FOR THIS SCOPE OF WORK ON THIS PROJECT. THE SUB-CONTRACTORS SHALL ALSO SCHEDULE ALL REQUIRED INSPECTIONS AND OBTAIN CERTIFICATES FOR HIS WORK, AT HIS EXPENSE.
- D. THE FOLLOWING SPECIFIC STANDARDS SHALL BE CONSIDERED AS MINIMUM REQUIREMENTS FOR WORK OF THIS SECTION:
 - 1. DUCTWORK: ALL DUCTWORK SHALL BE FABRICATED AND INSTALLED PER THE PUBLISHED STANDARDS OF THE AMERICAN SOCIETY OF HEATING, REFRIGERATION, AND AIR CONDITIONING ENGINEERS (ASHRAE) AND THE SHEET METAL AND AIR CONDITIONING NATIONAL ASSOCIATION (SMACNA), AND MEET THE REQUIREMENTS OF NFPA 90 AND NFPA 91.
 - 2. FILTERS: ALL FILTER MEDIA SHALL BE UL CLASS 2.
 - 3. FIRE DAMPERS: ALL FIRE DAMPERS SHALL BE LISTED AND INSTALLED PER UL FOR THE ASSEMBLY THEY ARE INSTALLED IN, AND MEET THE REQUIREMENTS OF THE LOCAL BUILDING CODE.

1.4 SUBMITTALS AND SUBSTITUTIONS

- A. SUBMITTAL MATERIALS SHALL BE COMPLETE IN EVERY RESPECT AND SHALL CLEARLY INDICATE EQUIPMENT FEATURES, DIMENSIONS, WEIGHTS, PERFORMANCE CHARACTERISTICS, AND CAPACITIES. CAPACITY AND PERFORMANCE CALCULATIONS SHALL BE ADJUSTED TO INDICATE ACTUAL EQUIPMENT PERFORMANCE AT THE PROJECT ELEVATION. LITERATURE OR DRAWINGS THAT DESCRIBE MORE THAN ONE MODEL OR SIZE OF EQUIPMENT SHALL BE MARKED WITH ARROWS OR OTHERWISE CLEARLY INSCRIBED TO IDENTIFY THE ACTUAL EQUIPMENT THAT WILL BE FURNISHED. ALL OPTIONS AND SPECIAL PARTS OF FEATURES SHALL ALSO BE CLEARLY IDENTIFIED. ALL SUBMITTED MATERIALS MUST BE CLEAR, COMPLETE, AND LEGIBLE. ALL SUBMITTALS OF THIS SCOPE MUST BE SUBMITTED AT ONE TIME; MULTIPLE AND VARIED SUBMITTALS WILL BE REJECTED.
- B. SUBMITTALS FOR ALL EQUIPMENT SHALL BE ROUTED THROUGH AND REVIEWED BY THE CONTRACTOR. THE CONTRACTOR SHALL CHECK ALL SUBMITTALS FOR ADEQUATE IDENTIFICATION, CORRECTNESS, AND COMPLIANCE WITH CONTRACT DRAWINGS AND SPECIFICATIONS AND APPLY A STAMP OF APPROVAL. FOR SUBMITTALS THAT ARE REQUIRED TO BE REVIEWED BY THE ENGINEER, A DIGITAL COPY SHALL BE FORWARDED FOR REVIEW AFTER REVIEW AND APPROVAL BY THE CONTRACTOR. THESE SHALL BE RETURNED AND SHALL BE RESUBMITTED UNTIL ACCEPTED BY THE ENGINEER. PROVIDE PRODUCT DATA FOR EACH PIECE OF EQUIPMENT/COMPONENT LISTED BELOW:
 - 1. AIR MOVING EQUIPMENT.
 - 2. GRILLES, REGISTERS, AND DIFFUSERS.
 - 3. EXHAUST HOODS.
 - 4. WHERE SEISMIC SUPPORT IS REQUIRED BY CODES, PROVIDE SHOP DRAWINGS AND SUPPORTING CALCULATIONS IN ACCORDANCE WITH THE ASCE 7 CHAPTER 13. CALCULATIONS AND SHOP DRAWINGS SHALL BE SIGNED AND SEALED BY A LICENSED ENGINEER IN THE STATE IN WHICH THE PROJECT SITE OCCURS.
 - C. APPROVED MANUFACTURERS, WHICH MAY SUBMIT EQUAL PRODUCT TO THOSE SPECIFIED, ARE LISTED IN THE EQUIPMENT SCHEDULES. ANY SUBMITTAL FOR CONSIDERATION AS AN EQUAL TO THAT SCHEDULED MUST CONTAIN ALL INFORMATION REQUIRED TO EVALUATE THIS CLAIM. MANUFACTURERS NOT LISTED AS EQUAL MUST SUBMIT IN WRITING FOR REVIEW FIVE DAYS PRIOR TO BID CLOSING. CONTRACTOR IS RESPONSIBLE TO ASSURE ANY SUBSTITUTED ITEM MEETS ALL PHYSICAL AND PERFORMANCE REQUIREMENTS AS INTENDED IN THE DESIGN DOCUMENTS.
 - D. APPROVED SUBMITTALS BY THE ENGINEER SHALL NOT RELIEVE THE CONTRACTOR FROM RESPONSIBILITY FOR DEVIATIONS FROM DRAWINGS OR SPECIFICATIONS, NOR SHALL IT RELIEVE HIM FROM RESPONSIBILITY FOR ERRORS IN SHOP DRAWINGS OR OTHER SUBMITTAL LITERATURE.
 - E. CONTRACTOR HAS SOLE RESPONSIBILITY TO COORDINATE ANY SUBSTITUTIONS WITH ALL OTHER DISCIPLINES. EQUIPMENT OF GREATER POWER, DIMENSIONS, CAPACITIES, AND RATINGS MAY BE FURNISHED PROVIDED SUCH PROPOSED EQUIPMENT IS APPROVED IN WRITING AND CONNECTING MECHANICAL AND ELECTRICAL SERVICES, CIRCUIT BREAKERS, CONDUIT, MOTORS, BASES, AND EQUIPMENT SPACES ARE INCREASED. NO ADDITIONAL COSTS WILL BE ACCEPTED FOR THESE INCREASES. IF LARGER EQUIPMENT IS PROVIDED, IF MINIMUM ENERGY RATINGS OR EFFICIENCIES OF THE EQUIPMENT ARE SPECIFIED, THE EQUIPMENT MUST MEET THE DESIGN REQUIREMENTS AND COMMISSIONING REQUIREMENTS. DESIGN OF ELECTRICAL REQUIREMENTS IS BASED ON MECHANICAL EQUIPMENT SPECIFIED. MECHANICAL CONTRACTOR SHALL COORDINATE WITH ELECTRICAL CONTRACTOR IF EQUIPMENT PURCHASED IS DIFFERENT FROM THAT SPECIFIED STILL MEETS DESIGN INTENT, INCLUDING BUT NOT LIMITED TO OVERCURRENT PROTECTION, LOCAL DISCONNECTION MEANS, WIRE SIZING, AND DESIGN COSTS.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. EQUIPMENT, MATERIALS, AND EQUIPMENT RECEIVED PROPERLY IDENTIFIED WITH NAMES, MODEL NUMBERS, TYPES, GRADES, COMPLIANCE LABELS, AND OTHER INFORMATION NEEDED FOR IDENTIFICATION.
- B. ALL MECHANICAL EQUIPMENT AND MATERIAL ITEMS SHALL BE PROTECTED FROM WEATHER AND VANDALISM PRIOR TO ACTUAL INSTALLATION. FAN WHEELS, PUMPS AND OTHER ROTATING MACHINERY SHALL BE PERIODICALLY ROTATED DURING STORAGE. ANY FACTORY PAINTED EQUIPMENT SCRATCHED OR MARRED DURING SHIPMENT OR CONSTRUCTION SHALL BE RESTORED TO ORIGINAL "NEW" CONDITION. THIS INCLUDES COMPLETE REPAINTING OF THE EQUIPMENT IF NECESSARY TO PROVIDE EXACT PAINT MATCH.
- C. CONTRACTOR IS RESPONSIBLE FOR RECEIVING AND OFFLOADING EQUIPMENT OF HIS SCOPE, IMMEDIATELY UPON RECEIPT, CONTRACTOR SHALL INSPECT ALL EQUIPMENT AND MATERIAL FOR SHIPPING DAMAGE AND REPLACE ANY DEFECTIVE ITEMS AT NO INCREASE TO CONTRACT AMOUNT.

1.6 SEQUENCING AND SCHEDULING

- A. COORDINATE MECHANICAL EQUIPMENT INSTALLATION WITH OTHER BUILDING COMPONENTS PRIOR TO ORDERING OR FABRICATION OF ADJOINING WORK.
- B. COORDINATE THE INSTALLATION OF REQUIRED SUPPORTING DEVICES AND SET SLEEVES IN POURED-IN-PLACE CONCRETE AND OTHER STRUCTURAL COMPONENTS AS THEY ARE CONSTRUCTED. ARRANGE FOR CHASES, SLOTS, AND OPENINGS IN BUILDING STRUCTURE DURING PROGRESS OF CONSTRUCTION TO ALLOW FOR MECHANICAL INSTALLATIONS.
- C. SEQUENCE, COORDINATE, AND INTEGRATE INSTALLATIONS OF MECHANICAL MATERIALS AND EQUIPMENT FOR EFFICIENT FLOW OF THE WORK. COORDINATE INSTALLATION OF LARGE EQUIPMENT REQUIRING POSITIONING PRIOR TO CLOSING IN THE BUILDING.
- D. COORDINATE CONNECTION OF MECHANICAL SYSTEMS WITH EXTERIOR UNDERGROUND AND OVERHEAD UTILITIES AND SERVICES. COMPLY WITH REQUIREMENTS OF GOVERNING REGULATIONS, FRANCHISED SERVICE COMPANIES, AND CONTROLLING AGENCIES. COORDINATE CONNECTION OF ELECTRICAL SERVICES.
- E. PROVIDE IDENTIFICATION OF ALL EQUIPMENT. COORDINATE INSTALLATION OF IDENTIFYING DEVICES AFTER COMPLETING COVERING AND PAINTING WHERE DEVICES ARE APPLIED TO SURFACES. INSTALL IDENTIFYING DEVICES PRIOR TO INSTALLING ACOUSTICAL CEILINGS AND SIMILAR CONCEALMENT.

1.7 PROJECT CLOSE-OUT

- A. CONTRACTOR SHALL FURNISH A WRITTEN GUARANTEE TO REPLACE OR REPAIR ANY DEFECTS IN WORKMANSHIP OR EQUIPMENT, WHICH DEVELOP WITHIN ONE YEAR FROM ACCEPTANCE BY THE OWNER. CONTRACTOR MUST ASSUME RESPONSIBILITY FOR ALL EXPENSES INCURRED TO REPAIR OR REPLACE HIS WORK AS WELL AS WORK OF OTHER TRADES THAT MAY BE AFFECTED BY THE REPAIR.
- B. CONTRACTOR SHALL TURN OVER TO THE OWNER THE SET OF CONSTRUCTION DRAWINGS SHOWING DEVIATIONS BETWEEN THE DRAWINGS AND INSTALLED CONDITIONS. THESE SHALL BE TURNED OVER TO THE OWNER AT ACCEPTANCE OF THE WORK.
- C. PROVIDE THREE (3) COMPLETE SETS OF OPERATION AND MAINTENANCE MANUALS. THESE ARE TO INCLUDE ALL EQUIPMENT CUT-SHEETS; MANUFACTURERS RECOMMENDED MAINTENANCE PROCEDURES, MANUFACTURERS WARRANTY INFORMATION, AND CONTRACTORS WARRANTY LETTER AND CONTACT INFORMATION.
- D. PROVIDE THREE (3) REVIEWED BALANCE REPORTS OF WATER AND AIR SYSTEMS AS APPLICABLE.
- E. CONTRACTOR SHALL INSTRUCT THE OWNER ON THE OPERATION AND MAINTENANCE OF ALL SYSTEMS PROVIDED UNDER THIS CONTRACT.

PART 2 - PRODUCTS

2.1 GENERAL

- A. DUCT DIMENSIONS SHOWN ON PLANS ARE NET FREE AREA.
- B. ROUND ELBOWS MUST HAVE A CENTERLINE RADIUS OF NO LESS THAN 1.5 TIMES THE DIAMETER OF THE ELBOW. SQUARE ELBOWS SHALL HAVE TURNING VANS.
- C. ALL DUCTWORK EXPOSED TO VIEW SHALL BE ROUND OR OVAL SPIRAL.

2.2 DUCTWORK MATERIALS

- A. COMPLY WITH SMACNA'S "HVAC DUCT CONSTRUCTION STANDARDS-METAL AND FLEXIBLE" FOR ACCEPTABLE MATERIALS, MATERIAL THICKNESS, AND DUCT CONSTRUCTION METHODS. UNLESS OTHERWISE INDICATED, SHEET METAL MATERIALS SHALL BE FREE OF PITTING, SEAM MARKS, BULLERS, STAINS, DISCOLORATIONS, AND OTHER IMPERFECTIONS. UNLESS STATED OTHERWISE, ALL DUCTWORK TO BE 26 GAUGE MINIMUM.
- B. GALVANIZED SHEET STEEL: LOCK-FORMING QUALITY; COMPLYING WITH ASTM A 633/A 653M AND HAVING G90 (Z275) COATING DESIGNATION; DUCTS SHALL HAVE MILL-PHOSPHATIZED FINISH FOR EXPOSED TO VIEW.
- C. CARBON-STEEL SHEETS: ASTM A 36/A 36M, COLD-ROLLED SHEETS; COMMERCIAL QUALITY; WITH OILED, MATTE FINISH FOR EXPOSED DUCTS.
- D. STAINLESS STEEL: ASTM A 480/A 480M, TYPE 316 OR 304, AND HAVING A NO. 2D FINISH FOR CONCEALED DUCTS AND SUITABLE FINISH FOR EXPOSED DUCTS.

2.3 INSULATION AND LINER

- A. GENERAL
 - 1. FIRE-HAZARD CLASSIFICATION: MAXIMUM FLAME-Spread INDEX OF 25 AND SMOKE-Developed INDEX OF 50 WHEN TESTED ACCORDING TO ASTM E 84.
 - 2. INSULATION SCHEDULE:
 - a. OUTSIDE THE BUILDING THERMAL ENVELOPE
 - b. INSIDE THE BUILDING THERMAL ENVELOPE
 - c. INSULATE ALL SUPPLY AND RETURN DUCTS TO R-8 INSIDE THE BUILDING THERMAL ENVELOPE
 - d. INSULATE SUPPLY AIR DUCTS TO R-6
 - e. INSULATE RETURN AIR DUCTS LOCATED IN UNCONDITIONED SPACES TO R-6
 - f. INSULATE OUTSIDE AIR DUCTS TO R-8 WITH CLOSED CELL INSULATION TO PREVENT CONDENSATION.
 - g. INSULATE ALL SUPPLY AND RETURN DUCTS INSULATION NOT REQUIRED.
- B. DUCT INSULATION: MINERAL OR GLASS FIBERS BONDED WITH A THERMOSETTING RESIN. COMPLY WITH ASTM C 553, TYPE II AND ASTM C 1290, TYPE III WITH FACTORY-APPLIED FSK JACKET.
- C. FIBROUS-GLASS LINER: COMPLY WITH NFPA 90A OR NFPA 90B AND WITH NAIMA AH124.
 - 1. MATERIALS: ASTM C 1071; SURFACES EXPOSED TO AIRSTREAM SHALL BE COATED TO PREVENT EROSION OF GLASS FIBERS.
 - 2. THICKNESS: 1"
 - 3. LINER ADHESIVE: COMPLY WITH NFPA 90A OR NFPA 90B AND WITH ASTM C 916.
 - 4. MECHANICAL FASTENERS: GALVANIZED STEEL SUITABLE FOR ADHESIVE ATTACHMENT, MECHANICAL ATTACHMENT, OR WELDING ATTACHMENT TO DUCT WITHOUT DAMAGING LINER WHEN APPLIED AS RECOMMENDED BY MANUFACTURER AND WITHOUT CAUSING DAMAGE IN DUCT.
- D. FIRE-RATED INSULATION SYSTEMS: HIGH-TEMPERATURE, FLEXIBLE, BLANKET INSULATION WITH FSK JACKET THAT IS UL TESTED AND CERTIFIED TO PROVIDE REQUIRED FIRE RATING.
- E. REFRIGERANT PIPING INSULATION: SUCTION PIPING - FLEXIBLE ELASTOMERIC, 1" THICK.

2.4 DUCT ACCESSORIES

- A. STANDARD VOLUME DAMPERS: SINGLE OR OPPOSED-BLADE DESIGN, STANDARD LEAKAGE RATING, AND SUITABLE FOR HORIZONTAL OR VERTICAL APPLICATIONS. SHAFTS TO BE FULL LENGTH, GALVANIZED STEEL, WITH ZINC-PLATED, DIE-CAST CORE, METAL DIAL AND HANDLE MADE OF 3/8-INCH THICK ZINC-PLATED STEEL, AND 3/4-INCH HEXAGON LOCKING NUT. INCLUDE CENTER HOUSING TO SUIT DAMPER OPERATING-ROD SIZE. INCLUDE ELEVATED PLATFORM FOR INSULATED DUCT MOUNTING.
- B. FIRE DAMPERS: CURTAIN TYPE: FIRE DAMPERS SHALL BE LABELED ACCORDING TO UL 555.
 - 1. FRAME: FABRICATED WITH ROLL-FORMED, 0.034-INCH THICK GALVANIZED STEEL, WITH MITERED AND INTERLOCKING CORNERS.
 - 2. BLADES: ROLL-FORMED, INTERLOCKING, 0.034-INCH THICK, GALVANIZED SHEET STEEL. IN PLACE OF INTERLOCKING BLADES, USE FULL-LENGTH, 0.034-INCH THICK, GALVANIZED STEEL BLADE CONNECTORS.
 - 3. FUSIBLE LINK: REPLACEABLE, 165 DEGREE F RATED.
- C. CEILING FIRE DAMPERS: LABELED ACCORDING TO UL 555C; COMPLY WITH CONSTRUCTION DETAILS FOR TESTED FLOOR- AND ROOF-CEILING ASSEMBLIES AS INDICATED IN UL'S FIRE RESISTANCE DIRECTORY.
- D. COMBINATION FIRE/SMOKE DAMPERS: LABELED ACCORDING TO UL 555. COMBINATION FIRE AND SMOKE DAMPERS SHALL BE LABELED ACCORDING TO UL 155 FOR 1-HOUR RATING.
 - 1. FRAME AND BLADES: 0.064-INCH THICK, GALVANIZED SHEET STEEL.
 - 2. MOUNTING SLEEVE: FACTORY-INSTALLED, 0.052-INCH THICK, GALVANIZED SHEET STEEL; LENGTH TO SUIT WALL OR CEILING.
 - 3. FUSIBLE LINK: REPLACEABLE, 165 DEGREE F RATED.
 - 4. DAMPER MOTORS: MODULATING AND TWO-POSITION ACTION. EQUIP WITH AN INTEGRAL SPIRAL-SPRING MECHANISM WHERE INDICATED. ENCLOSE ENTIRE SPRING MECHANISM IN A REMOVABLE HOUSING DESIGNED FOR SERVICE OR ADJUSTMENTS.
 - 5. ELECTRICAL CONNECTION: 115V, SINGLE PHASE, 60 HZ.
 - 6. SMOKE DETECTOR: INTEGRAL, FACTORY WIRED FOR SINGLE-POINT CONNECTION, COORDINATE WITH ELECTRICAL CONTRACTOR AND FIRE ALARM CONTRACTOR.
 - 7. FLEXIBLE CONNECTORS: FLAME-RETARDANT OR NONCOMBUSTIBLE FABRICS, COATINGS, AND ADHESIVES COMPLYING WITH UL 181, CLASS 1. PROVIDE HEAVY METAL EDGE BANDS, SEALED TO PREVENT LEAKAGE.
 - 8. INDOOR SYSTEM: FLEXIBLE CONNECTOR FABRIC: GLASS FABRIC DOUBLE COATED WITH NEOPRENE.
 - 9. OUTDOOR SYSTEM: FLEXIBLE CONNECTOR FABRIC: GLASS FABRIC DOUBLE COATED WITH WEATHERPROOF, SYNTHETIC RUBBER RESISTANT TO UV RAYS AND OZONE.
 - 10. FLEXIBLE DUCTS: UL 181, CLASS 1, BLACK POLYMER FILM SUPPORTED BY HELICALLY WOUND, SPRING-STEEL WIRE; 1-1/2" FIBROUS-GLASS INSULATION; POLYETHYLENE VAPOR BARRIER FILM. FLEX DUCT SHALL BE EQUAL TO CERTAINTEED "CERTAFLEX" G25.

2.5 ACCESS DOORS AND PANELS

- A. DUCT MOUNTED ACCESS DOORS: DOUBLE WALL, DUCT MOUNTING, AND RECTANGULAR; FABRICATED OF GALVANIZED SHEET METAL WITH INSULATION FILLED AND THINNESS AS INDICATED FOR DUCT PRESSURE CLASS.
- B. FRAME: GALVANIZED SHEET STEEL, WITH REND-OVER TABS AND FOAM GASKETS.
- C. PROVIDE NUMBER OF HINGES AND LOCKS AS FOLLOWS:
 - a. LESS THAN 12 INCHES SQUARE: SECURE WITH TWO SASH LOCKS.
 - b. UP TO 18 INCHES SQUARE: TWO HINGES AND TWO SASH LOCKS.
 - c. UP TO 24 BY 48 INCHES: THREE HINGES AND TWO COMPRESSION LATCHES.
- D. EQUIPMENT CURBS AND SUPPORT:
 - 1. ROOF MOUNTED EQUIPMENT: PROVIDE FACTORY CURB TO MATCH EQUIPMENT PROVIDED. CURB TO MATCH ROOF SLOPE, TYPE, AND INSULATION DEPTHS FOR PROPER EQUIPMENT MOUNTING (ACCOUNT FOR APPLICABLE ACCESSORIES SUCH AS ECONOMIZERS AND ERVS).
 - 2. GROUND/FLOOR MOUNTED EQUIPMENT: PROVIDE CONCRETE HOUSE-KEEPING PAD AT LEAST 4" THICK AND AT LEAST 6" LARGER THAN THE EQUIPMENT BEING SUPPORTED.


2.6 TESTING AND BALANCING

- A. PERFORM TESTS AND BALANCING PROCEDURES ON EACH SYSTEM ACCORDING TO THE PROCEDURES CONTAINED IN NEBB'S "PROCEDURES FOR TESTING, ADJUSTING, AND BALANCING OF HVAC SYSTEMS" OR SMACNA'S "HVAC SYSTEMS - TESTING, ADJUSTING, AND BALANCING".
- B. PREPARE TEST REPORTS FOR BOTH FANS AND OUTLETS. OBTAIN MANUFACTURER'S OUTLET FACTORS AND RECOMMENDED TESTING PROCEDURES. CROSSCHECK THE SUMMATION OF REQUIRED OUTLET VOLUMES WITH REQUIRED FAN VOLUMES.
- C. ADJUST TERMINAL OUTLETS AND INLETS FOR EACH SPACE TO INDICATED AIRFLOWS WITHIN SPECIFIED TOLERANCES OF INDICATED VALUES. MAKE ADJUSTMENTS USING VOLUME DAMPERS RATHER THAN EXTRACTORS AND THE DAMPERS AT AIR TERMINALS.
- D. PREPARE TEST REPORTS WITH PERTINENT DESIGN DATA AND NUMBER IN SEQUENCE STARTING AT PUMP TO END OF SYSTEM. CHECK THE SUM OF BRANCH/CIRCUIT FLOWS AGAINST APPROVED PUMP FLOW RATE. CORRECT VARIATIONS THAT EXCEED PLUS OR MINUS 5 PERCENT.

2.7 CONTROLS AND ELECTRICAL COMPONENTS

- A. WHERE REQUIRED, CONTRACTOR SHALL FURNISH A COMBINATION STARTER


Exhibit B



3/28/2025 4:59:58 PM

9 SECOND FLOOR MECHANICAL / ELECTRICAL DEMOLITION PLAN

SCALE: 1/4" = 1'-0"



1 SECOND FLOOR - SELF HELP - RCP DEMOLITION PLAN

SCALE: 1/4" = 1'-0"

NORTH

issue date
04.24.2025

Page 9/10

issue date
04.24.2025

M2.0

SPECIFIC SHEET NOTES	
1. E.C. SHALL CAUTIOUSLY REMOVE EXISTING CARD READER, SAVE FOR RELOCATION, REPAIR WALL TO MATCH ADJACENT FINISHES, PER ARCHITECTURAL.	
2. E.C. TO REMOVE EXISTING LIGHT, FOR RELOCATION IN NEW CEILING, REFERENCE ARCHITECTURAL.	
3. E.C. SHALL CAUTIOUSLY REMOVE EXISTING SMOKE ALARM, TO BE RELOCATED IN NEW CEILING, REFERENCE ARCHITECTURAL.	
4. M.C. SHALL CAUTIOUSLY REMOVE CEILING AROUND EXISTING SPRINKLER HEAD, TO BE RELOCATED, AND REROUTED AS NECESSARY IN NEW CEILING, REFERENCE ARCHITECTURAL.	
5. M.C. TO REMOVE TRANSFER GRILLE, SAVE FOR RELOCATION IN NEW CEILING, REFERENCE ARCHITECTURAL.	

ELECTRICAL PROJECT NOTES	
1. THIS PROJECT CONSISTS OF REMOVING, RELOCATING, AND FURNISHING NEW ELECTRICAL WORK IN THE REDESIGNED 2ND LEVEL SELF HELP AREA AT THE MISSOULA COUNTY COURTHOUSE, OWNER IS THE MISSOULA COUNTY.	
2. E.C. SHALL BE COGNIZANT THAT THIS IS A REMODELING PROJECT AND CERTAIN DETAILS AND ITEMS CANNOT BE FULLY EXPLAINED WITHOUT FIELD OBSERVATION. E.C. SHALL VISIT AND EXAMINE THE PROJECT AREA AND MAKE ALLOWANCES IN THEIR PROPOSAL FOR ALL CONDITIONS IMPACTING THEIR WORK.	
3. THESE DRAWINGS HAVE BEEN PREPARED USING SITE INVESTIGATIONS AND PROVIDED RECORD DRAWINGS OF THE PROJECT AREA. NONE OF THE EXISTING BRANCH CIRCUITS OR THEIR PANEL DIRECTORIES HAVE BEEN VERIFIED. E.C. SHALL VERIFY EXISTING CONDITIONS AND INCLUDE IN THEIR BID A SUFFICIENT SUM OF MONEY TO COVER ANY DISCREPANCY BETWEEN THE DRAWINGS AND THE PROJECT'S EXISTING CONDITIONS.	
4. ALL ITEMS (INCLUDING ALL ASSOCIATED OUTLET BOXES, WIRES, AND CONDUIT SUPPORTS) THAT ARE TO BE REMOVED SHALL BE REMOVED COMPLETELY TO THE LAST ACTIVE JUNCTION BOX FOR BRANCH CIRCUITS TO REMAIN, OR TO THE ELECTRICAL PANEL FOR COMPLETELY REMOVED BRANCH CIRCUITS.	
5. E.C. SHALL TERMINATE ALL CONDUCTORS, RACEWAYS, ENCLOSURES, AND OTHER ELECTRICAL EQUIPMENT PROPERLY AND SECURELY.	
6. ALL TEMPORARY HAZARDOUS EXPOSURES SHALL BE PROPERLY ENCLOSED, GUARDED, BARRIERED, OR BARRACADED AT ALL TIMES TO PROTECT NON-ELECTRICAL PERSONNEL.	
7. E.C. SHALL COORDINATE ALL COMMUNICATIONS UTILITIES (VOICE, DATA, SECURITY, TELEVISION, ETC.) WITH THE OWNER AND THE OWNER'S SUBCONTRACTORS PRIOR TO PERFORMING THE ROUGH-IN OF THE RACEWAYS, BOXES, AND CABLING INSTALLATIONS.	
8. E.C. SHALL FURNISH COMPLETE ELECTRICAL SYSTEMS FOR ALL WORK THEY ARE BIDDING. E.C. SHALL INFORM THE ENGINEER OF ALL CONSTRUCTION ISSUES PRIOR TO PLACING THEIR BID THAT MAY IMPACT THEIR WORK AND CONTRACT BID AMOUNT.	
9. E.C. SHALL BE RESPONSIBLE FOR ALL LINE VOLTAGE AND FIRE ALARM WIRING, COMMUNICATIONS, AND SPECIAL SYSTEMS RACEWAYS IN THIS PROJECT.	
10. E.C. SHALL COORDINATE THEIR WORK WITH ALL OTHER TRADES.	
11. E.C. SHALL FURNISH NEW, UPDATED PANEL DIRECTORIES FOR PANELS WHERE BRANCH CIRCUIT ADDITIONS, MODIFICATIONS, AND REMOVALS OCCUR. BRANCH CIRCUITS INDICATED ON THESE DRAWINGS ARE FROM THE RECORD DRAWINGS' PANEL SCHEDULES.	
12. CONTRACTOR IS RESPONSIBLE FOR COORDINATING POWER CONNECTIONS TO FIRE SMOKE DAMPERS.	

GENERAL MECHANICAL NOTES	
A. THE CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFYING ALL UTILITIES, PIPING, UNDERGROUND WIRING, TELEPHONE, TV AND/OR SATELLITE DISH CABLES, ETC. BEFORE WORK BEGINS.	
B. EQUIPMENT, MECHANICAL PIPING AND DUCTWORK INDICATED IS PARTIALLY DIAGRAMMATIC. CONTRACTOR SHALL DETERMINE IN FIELD EXACT LOCATION OF ALL DUCTWORK, PIPING AND EQUIPMENT. CONTRACTOR SHALL COORDINATE WITH ALL OTHER TRADES PRIOR TO INSTALLATION OF HISHER EQUIPMENT.	
C. UPON COMPLETION OF WORK THE CONTRACTOR SHALL CLEAN ALL DEBRIS FROM THE WORK AREA AND OTHER AREAS USED BY THE CONTRACTOR, AND LEAVE PREMISES IN A NEAT AND CLEAN CONDITION. CLEAN, PATCH AND REPAIR ALL WALLS, FLOORS, CEILINGS, AND OTHER SURFACES DAMAGED OR MARKED DURING CONSTRUCTION.	
D. ALL WORK SHALL COMPLY WITH THE MOST STRINGENT OF APPLICABLE CODES, ORDINANCES, AND REQUIREMENTS BY THE OWNER AND MANUFACTURER.	
E. COORDINATE DIFFUSER/GRILLE LOCATIONS WITH ARCHITECT.	
F. INSULATE ALL PIPING & DUCTWORK COMPLETE IN ACCORDANCE WITH THE PLANS, SPECIFICATIONS AND APPLICABLE ENERGY CODE. INSULATION WORK SHALL BE PERFORMED BY A COMPANY WHOSE PRIMARY FUNCTION IS MECHANICAL INSULATION INSTALLED BY STAFF WITH A MINIMUM OF THREE YEARS DOCUMENTED EXPERIENCE.	
G. CONTRACTOR SHALL THOROUGHLY CLEAN ALL DUCTWORK AND EQUIPMENT COMPLETE AND INSTALL NEW FILTERS PRIOR TO AIR BALANCE. ALL DUCTWORK OPENINGS INCLUDING GRILLES AND DIFFUSERS SHALL BE SEALED AIR TIGHT UNTIL CONSTRUCTION IS 100% COMPLETE AND FINAL CLEANING HAS BEEN COMPLETED.	
H. INSTALL ALL EQUIPMENT IN STRICT ACCORDANCE WITH MANUFACTURERS WRITTEN INSTRUCTIONS.	
I. COORDINATE ALL MECHANICAL PIPING & DUCTWORK PENETRATIONS WITH STRUCTURAL PLANS AND SCHEDULES. CRITICAL INSTALLATION AREAS ARE INDICATED WITH DIMENSIONS.	
J. INSTALL FLEXIBLE DUCT CONNECTIONS AT ALL UNIT CONNECTIONS. ALL SUSPENDED EQUIPMENT SHALL BE ISOLATED FROM THE STRUCTURE WITH SPRING VIBRATION ISOLATORS AND KELLET PADS.	
K. INSTALL ALL SLAB MOUNTED EQUIPMENT EXCEPT FOR TANKS ON KELLET ISOLATOR PADS - NO EXCEPTIONS.	
L. FOR HYDROMIC/HVAC PIPING SYSTEMS, BRASS VALVES SHALL BE USED EXCLUSIVELY IN ALL AREAS OUTSIDE OF MECHANICAL ROOMS. THIS VALVE REQUIREMENT SHALL SUPERSEDE DIVISION 22 AND 23 SPECIFICATIONS.	

SECOND FLOOR MECH/ELECT. DEMOLITION PLANS

MISSOULA COUNTY COURTHOUSE SELF HELP MOVE
200 WEST BROADWAY, 2ND FLOOR
MISSOULA COUNTY, 200 WEST BROADWAY STREET, MISSOULA, MT 59802

sheet project
project # 25004.0
AEG # 24045
revision date


phase
CONSTRUCTION DOCUMENTS

a&e

Page 9/10


issue date
04.24.2025

M2.0



AXIOM
ENGINEERING GROUP
910 Brooks St, #203
Missoula, MT 59801
Ph: 406.242.2649
www.aeg.design

Exhibit B




SPECIFIC SHEET NOTES


1. E.C. SHALL REINSTALL CARD READER TO THIS LOCATION.
2. E.C. SHALL PROVIDE AND INSTALL NEW CARD READER AT THIS LOCATION.
3. M.C. TO INSTALL TRANSFER GRILLE FOR AIR TRANSFER FROM MAIN (NORTH) HALL INTO NEW HALLWAY. 6X6, 4X10 OR SIMILAR SIZED GRILLE TO ACCOMODATE APPROXIMATE 60CFM FLOW.
4. M.C. TO INSTALL TRANSFER GRILLE FOR AIR TRANSFER FROM HALLWAY INTO RESTROOM. 6X6, 4X10 OR SIMILAR GRILLE TO ACCOMODATE APPROXIMATE 60CFM FLOW.
5. E.C. TO RELOCATE LIGHT IN NEW CEILING, REFERENCE ARCHITECTURAL.
6. E.C. TO RELOCATE EXISTING SMOKE ALARM IN NEW CEILING, REFERENCE ARCHITECTURAL.
7. M.C. TO REROUTE AND RELOCATE SPRINKLER HEAD AS NECESSARY IN NEW CEILING, REFERENCE ARCHITECTURAL.
8. M.C. TO RELOCATE TRANSFER GRILLE IN NEW CEILING, REFERENCE ARCHITECTURAL.

GENERAL MECHANICAL NOTES

- A. THE CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFYING ALL UTILITIES, PIPING, UNDERGROUND WIRING, TELEPHONE, TV AND/OR SATELLITE DISH CABLES, ETC. BEFORE WORK BEGINS.
- B. EQUIPMENT, MECHANICAL PIPING AND DUCTWORK INDICATED IS PARTIALLY DIAGRAMMATIC. CONTRACTOR SHALL DETERMINE IN FIELD EXACT LOCATION OF ALL DUCTWORK, PIPING AND EQUIPMENT. CONTRACTOR SHALL COORDINATE WITH ALL OTHER TRADES PRIOR TO INSTALLATION OF HIS/HER EQUIPMENT.
- C. UPON COMPLETION OF WORK THE CONTRACTOR SHALL CLEAN ALL DEBRIS FROM THE WORK AREA AND OTHER AREAS USED BY THE CONTRACTOR, AND LEAVE PREMISES IN A NEAT AND CLEAN CONDITION. CLEAN, PATCH AND REPAIR ALL WALLS, FLOORS, CEILINGS, AND OTHER SURFACES DAMAGED OR MARKED DURING CONSTRUCTION.
- D. ALL WORK SHALL COMPLY WITH THE MOST STRINGENT OF APPLICABLE CODES, ORDINANCES, AND REQUIREMENTS BY THE OWNER AND MANUFACTURER.
- E. COORDINATE DIFFUSER/GRILLE LOCATIONS WITH ARCHITECT.
- F. INSULATE ALL PIPING & DUCTWORK COMPLETE IN ACCORDANCE WITH THE PLANS, SPECIFICATIONS AND APPLICABLE ENERGY CODE. INSULATION WORK SHALL BE PERFORMED BY A COMPANY WHOSE PRIMARY FUNCTION IS MECHANICAL INSULATION INSTALLATION. CONTRACTOR SHALL HAVE A MINIMUM OF THREE YEARS DOCUMENTED EXPERIENCE.
- G. CONTRACTOR SHALL THOROUGHLY CLEAN ALL DUCTWORK AND EQUIPMENT COMPLETE AND INSTALL NEW FILTERS PRIOR TO AIR BALANCE. ALL DUCTWORK OPENINGS INCLUDING GRILLES AND DIFFUSERS SHALL BE SEALED AIR TIGHT UNTIL CONSTRUCTION IS 100% COMPLETE AND FINAL CLEANING HAS BEEN COMPLETED.
- H. INSTALL ALL EQUIPMENT IN STRICT ACCORDANCE WITH MANUFACTURERS WRITTEN INSTRUCTIONS.
- I. COORDINATE ALL MECHANICAL PIPING & DUCTWORK PENETRATIONS WITH STRUCTURAL PLANS AND SCHEDULES. CRITICAL INSTALLATION AREAS ARE INDICATED WITH DIMENSIONS.
- J. INSTALL FLEXIBLE DUCT CONNECTIONS AT ALL UNIT CONNECTIONS. ALL SUSPENDED EQUIPMENT SHALL BE ISOLATED FROM THE STRUCTURE WITH SPRING VIBRATION ISOLATORS AND KELLET PADS.
- K. INSTALL ALL SLAB MOUNTED EQUIPMENT EXCEPT FOR TANKS ON KELLET ISOLATOR PADS - NO EXCEPTIONS.
- L. FOR HYDRONIC/HVAC PIPING COMPLETE.
- M. FOR HYDRONIC/HVAC PIPING SYSTEMS, BRASS VALVES SHALL BE USED EXCLUSIVELY IN ALL AREAS OUTSIDE OF MECHANICAL ROOMS. THIS VALVE REQUIREMENT SHALL SUPERSEDE DIVISION 22 AND 23 SPECIFICATIONS.



9 SECOND FLOOR MECHANICAL / ELECTRICAL NEW PLAN
SCALE: 1/4" = 1'-0"



11 SECOND FLOOR - SELF HELP - ELECTRICAL NEW PLAN
SCALE: 1/4" = 1'-0"

SECOND FLOOR MECH/ELECT. NEW PLANS

MISSOULA COUNTY COURTHOUSE SELF HELP MOVE

200 WEST BROADWAY, 2ND FLOOR
MISSOULA COUNTY, 200 WEST BROADWAY STREET, MISSOULA, MT 59802

sheet project project
project # 25004.0
AEG # 24045
revision date

phase
CONSTRUCTION DOCUMENTS

a&e

Page 10/10

issue date
04.24.2025

M2.1